










DAB Evotron hringrásardælur

	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-27w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="528 667 1431 790"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>Evotron 40/130 1"</td> <td>286543355</td> <td>130mm</td> <td>1"</td> <td>4mtr</td> <td>45 l/min</td> </tr> <tr> <td colspan="6"><i>sbr.alpha 15/40</i></td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	Evotron 40/130 1"	286543355	130mm	1"	4mtr	45 l/min	<i>sbr.alpha 15/40</i>					
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
Evotron 40/130 1"	286543355	130mm	1"	4mtr	45 l/min														
<i>sbr.alpha 15/40</i>																			
	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-27w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="528 1093 1431 1216"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>Evotron 40/130</td> <td>286543361</td> <td>130mm</td> <td>1 1/2"</td> <td>4mtr</td> <td>45 l/min</td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	Evotron 40/130	286543361	130mm	1 1/2"	4mtr	45 l/min						
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
Evotron 40/130	286543361	130mm	1 1/2"	4mtr	45 l/min														
	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-27w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="528 1518 1431 1641"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>Evotron 40/180</td> <td>286543358</td> <td>180</td> <td>1 1/2"</td> <td>4 mtr</td> <td>45 l/min</td> </tr> <tr> <td colspan="6"><i>sbr.alpha 25/40</i></td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	Evotron 40/180	286543358	180	1 1/2"	4 mtr	45 l/min	<i>sbr.alpha 25/40</i>					
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
Evotron 40/180	286543358	180	1 1/2"	4 mtr	45 l/min														
<i>sbr.alpha 25/40</i>																			

DAB Evotron hringrásardælur

	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-43w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="536 667 1430 790"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>Evotron 60/130 1"</td> <td>286543356</td> <td>130mm</td> <td>1"</td> <td>6 mtr</td> <td>60 l/min</td> </tr> <tr> <td colspan="6"><i>sbr.alpha 15/60</i></td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	Evotron 60/130 1"	286543356	130mm	1"	6 mtr	60 l/min	<i>sbr.alpha 15/60</i>					
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
Evotron 60/130 1"	286543356	130mm	1"	6 mtr	60 l/min														
<i>sbr.alpha 15/60</i>																			
	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-43w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="536 1090 1430 1214"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>60/130</td> <td>286543303</td> <td>130mm</td> <td>1 1/2"</td> <td>6mtr</td> <td>60 l/min</td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	60/130	286543303	130mm	1 1/2"	6mtr	60 l/min						
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
60/130	286543303	130mm	1 1/2"	6mtr	60 l/min														
	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-43w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="536 1516 1430 1637"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>Evotron 60/180</td> <td>286543359</td> <td>180</td> <td>1 1/2"</td> <td>6 mtr</td> <td>60 l/min</td> </tr> <tr> <td colspan="6"><i>sbr.alpha 25/60</i></td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	Evotron 60/180	286543359	180	1 1/2"	6 mtr	60 l/min	<i>sbr.alpha 25/60</i>					
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
Evotron 60/180	286543359	180	1 1/2"	6 mtr	60 l/min														
<i>sbr.alpha 25/60</i>																			

DAB Evotron hringrásardælur

	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-66w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="528 667 1430 786"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>Evotron 80/130 1"</td> <td>286543357</td> <td>130mm</td> <td>1"</td> <td>8mtr</td> <td>70 l/min</td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	Evotron 80/130 1"	286543357	130mm	1"	8mtr	70 l/min						
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
Evotron 80/130 1"	286543357	130mm	1"	8mtr	70 l/min														
	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-66w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="528 1077 1430 1205"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>80/130</td> <td>286543360</td> <td>130mm</td> <td>1 1/2"</td> <td>8mtr</td> <td>70 l/min</td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	80/130	286543360	130mm	1 1/2"	8mtr	70 l/min						
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
80/130	286543360	130mm	1 1/2"	8mtr	70 l/min														
	<p>DAB EVOTRON Orkusparandi álagsstýrð hringrásardæla fyrir miðstöðvar og kælikerfi</p> <p>Polir hitastig á vökva frá -10°C til 110°C Hámarks vinnuþrýstingur er 10 bör. Orkueyðsla 5w-66w 1x230V Hámarks styrkleiki frostlögs er 30%</p> <table border="1" data-bbox="528 1496 1430 1624"> <thead> <tr> <th>Módel</th> <th>Vörunúmer</th> <th>lengd</th> <th>gengjust.</th> <th>lyftihæð</th> <th>afköst</th> </tr> </thead> <tbody> <tr> <td>Evotron 80/180</td> <td>286543360</td> <td>180</td> <td>1 1/2"</td> <td>8 mtr</td> <td>70 l/min</td> </tr> <tr> <td><i>sbr.alpha 25/80</i></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst	Evotron 80/180	286543360	180	1 1/2"	8 mtr	70 l/min	<i>sbr.alpha 25/80</i>					
Módel	Vörunúmer	lengd	gengjust.	lyftihæð	afköst														
Evotron 80/180	286543360	180	1 1/2"	8 mtr	70 l/min														
<i>sbr.alpha 25/80</i>																			